



Troughing SureGuide Spec Sheet

Item Code	Belt Width	Bracket to Bracket "A"	Bolt Hole "B"	Centre Roller Height "C"	Wing Roller Height "D"	Angle of Inclination "E"	Wing Roller Length "F"	Idler Gauge "G"	Idler Face "H"
	in mm	Stringer Length mm	in mm	in mm	in mm	Degrees	In mm	in mm	in mm
3-Roller System									
TSG45/3/35	450	686	100 & 240	177	281	35°	472	200	190
TSG60/3/35	600	838	100 & 240	177	310	35°	604	250	240
TSG75/3/35	750	990	100 & 240	177	339	35°	736	300	290
TSG90/3/35	900	1144	100 & 240	177	367	35°	868	350	340
TSG105/3/35	1050	1296	100 & 240	177	396	35°	1000	400	390
TSG120/3/35	1200	1448	100 & 240	177	430	35°	1158	460	450
HEAVY DUTY 3-Roller									
TSGHD105/3/35	1050	1296	546	520	485	35°	989	400	390
TSGHD120/3/35	1200	1448	240	263-270	520	35°	1146	460	450
TSGHD135/3/35	1350	1600	240	263-270	548	35°	1279	510	500
TSGHD150/3/35	1500	1752	240	263-270	583	35°	1437	570	560
TSGHD165/3/35	1650	1904	240	263-270	611	35°	1569	620	610
TSGHD180/3/35	1800	2058	240	263-270	640	35°	1701	670	660
TSGHD200/3/35	2000	2260	240	263-270	686	35°	1912	750	740
TSGHD210/3/35	2100	2362	240	263-270	701	35°	1978	775	765

